APPLIED TEXTILES
LAB SERVICES

CERTIFICATE OF TESTING

For The Account Of: **Pollack**
150 Varick Street
New York, NY 10013

DATE: November 14, 2006 CERTIFICATE (ORDER) NO.: 18303

CLIENT'S IDENTIFICATION: A Touch of the Bubbly 1041

CAL117, Section E, Part I - Upholstery Fabrics (CS 191-53) Raised Surface

Specimen	Flame Spread **Warp** (seconds)	With Nap (Raised Surface) **FACE**	Specimen	Flame Spread **Warp** (seconds)	With Nap (Raised Surface) **BACK**
1	DNI	X	1		
2	DNI	X	2		
3	DNI	X	3		
4			4	DNI	X
5			5	DNI	X

Specimen	Flame Spread **Fill** (seconds)	With Nap (Raised Surface) **FACE**	Specimen	Flame Spread **Fill** (seconds)	With Nap (Raised Surface) **BACK**
1	DNI	X	1		
2	DNI	X	2		
3	DNI	X	3		
4			4	DNI	X
5			5	DNI	X

- **DNI - Did not ignite when exposed to test ignition source**
- **IBE - Ignited but extinguished before burning through stop cord.**
- **SF - Surface flash only; stopcord not burned & no burning/charring/fusing of the base fabric.**
- **TSF - Timed surface flash; stopcord burned, but no burning/charring/fusing of the base fabric.**

Requirements: With nap - Minimum flame spread of any individual specimens shall be 7 seconds.
Requirements: Without nap - Minimum flame spread of any individual specimens shall be 3.5 seconds.
Conclusion: The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Lab Manager: Sallie Cotey

Jennifer Friend
Lab Technician: Jennifer Friend

A TEXTILE TESTING COMPANY
555 76TH STREET S.W., BYRON CENTER, MICHIGAN 49315
TELEPHONE 616.559.6123 FACSIMILE 616.559.6119