

## CERTIFICATE OF TESTING

For the Account Of: **Pollack**  
150 Varick Street  
New York, NY 10013

Contact: Larry Hoysic

Client's Identification: Equus 4176

**TEST PERFORMED** California Technical Bulletin 117, Section E (CPS 16 CFR 1610 – CS 191-53) Upholstery Fabrics, March 2000

**TEST RESULTS**

Plain Surface       Raised Surface

Specimen	Flame Spread Warp Face (s)	Flame Spread Warp Back (s)
1	DNI	
2	DNI	
3	DNI	
4		DNI
5		DNI

  

Specimen	Flame Spread Fill Face (s)	Flame Spread Fill Back (s)
1	DNI	
2	DNI	
3	DNI	
4		DNI
5		DNI

**ABBREVIATIONS USED**

**DNI** Did not ignite when exposed to test ignition source  
**IBE** Ignited but extinguished before burning through stop cord  
**SF** Surface flash only; stop cord not burned & no burning/charring/fusing of the base fabric  
**TSF** Timed surface flash; stop cord burned, but no burning/charring/fusing of the base fabric

**ACCEPTANCE CRITERIA**

- With nap** Minimum flame spread of any individual specimens shall be 7 seconds. (ACT Criteria decreases minimum time to 4 seconds)
- Without nap** Minimum flame spread of any individual specimens shall be 3.5 seconds.

**CONCLUSION**

Based on the above Results and Acceptance Criteria, the item tested:  
 Complies  
 Does Not Comply

**CERTIFICATION** I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.



Authorized Signature-MB