



CERTIFICATE OF TESTING

For The Account Of: **Pollack**
 150 Varick Street
 New York, NY 10013-1218
 Contact: Susan Whalen

DATE: September 26, 2001 CERTIFICATE (ORDER) NO.: 92886

CLIENT'S IDENTIFICATION: **5031 Tailor Made**

| |
|---|
| CAL117, Section E, Part I - Upholstery Fabrics |
|---|

Date Samples Were Received: September 26, 2001

| | <u>Flame Spread Warp</u> (seconds) | With Nap (Raised Surface) FACE | Without Nap (Plain Surface) FACE | With Nap (Raised Surface) BACK | Without Nap (Plain Surface) BACK |
|----------|---------------------------------------|---|---|---|---|
| Specimen | | | | | |
| 1 | NS | | X | | X |
| 2 | NS | | X | | X |
| 3 | NS | | X | | X |
| 4 | NS | | X | | X |
| 5 | NS | | X | | X |

| | <u>Flame Spread Fill</u> (seconds) | With Nap (Raised Surface) FACE | Without Nap (Plain Surface) FACE | With Nap (Raised Surface) BACK | Without Nap (Plain Surface) BACK |
|----------|---------------------------------------|---|---|---|---|
| Specimen | | | | | |
| 1 | NS | | X | | X |
| 2 | NS | | X | | X |
| 3 | NS | | X | | X |
| 4 | NS | | X | | X |
| 5 | NS | | X | | X |

* **NS - No flame spread (Non-Ignition)**

Requirements: With nap - Minimum flame spread of any individual specimens shall be less than 7 seconds.


Requirements: Without nap - Minimum flame spread of any individual specimens shall be less than 3.5 seconds.

Conclusion: The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Testing Completed: 09-27-01

Lab Manager: Sallie Cotey


 Jennifer Friend - Lab Technician