

CERTIFICATE OF TESTING

For The Account Of: **Pollack**
 150 Varick Street
 New York, NY 10013
 Contact: Susan Whalen

DATE: July 18, 2003 CERTIFICATE (ORDER) NO.: 10531

CLIENT'S IDENTIFICATION: **5046 Embellished Plush**

CAL117, Section E, Part I - Upholstery Fabrics (CS 191-53) Raised Surface

Specimen	<u>Flame Spread Warp</u> (seconds)	With Nap (Raised Surface) FACE	Specimen	<u>Flame Spread Warp</u> (seconds)	With Nap (Raised Surface) BACK
	1	DNI		X	1
2	DNI	X	2	DNI	X
3	DNI	X	3	DNI	X
4	DNI	X	4	DNI	X
5	DNI	X	5	DNI	X

Specimen	<u>Flame Spread Fill</u> (seconds)	With Nap (Raised Surface) FACE	Specimen	<u>Flame Spread Fill</u> (seconds)	With Nap (Raised Surface) BACK
	1	DNI		X	1
2	DNI	X	2	DNI	X
3	DNI	X	3	DNI	X
4	DNI	X	4	DNI	X
5	DNI	X	5	DNI	X

- **DNI - Did not ignite when exposed to test ignition source**
- **IBE - Ignited but extinguished before burning through stop cord.**
- **SF - Surface flash only; stopcord not burned & no burning/charring/fusing of the base fabric.**
- **TSF - Timed surface flash; stopcord burned, but no burning/charring/fusing of the base fabric.**


Requirements: With nap - Minimum flame spread of any individual specimens shall be less than 7 seconds.

Requirements: Without nap - Minimum flame spread of any individual specimens shall be less than 3.5 seconds.

Conclusion: The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Lab Manager: Sallie Cotey


 Lab Technician: Jennifer Friend