



## CERTIFICATE OF TESTING

DATE: September 17, 2004      CERTIFICATE (ORDER) NO.: 12171

CLIENT'S IDENTIFICATION:    **5048 Colorific**

|   |
|---|
| <b>CAL117, Section E, Part I - Upholstery Fabrics (CS 191-53) Plain Surface</b> |
|---|

| Specimen | <u>Flame Spread Warp</u><br>(seconds) | Without Nap<br>(Plain Surface)<br><b>FACE</b> | Specimen | <u>Flame Spread Warp</u><br>(seconds) | Without Nap<br>(Plain Surface)<br><b>BACK</b> |
|----------|---------------------------------------|---|----------|---------------------------------------|---|
| 1        | DNI                                   | X   | 1        | DNI                                   | X   |
| 2        | DNI                                   | X   | 2        | DNI                                   | X   |
| 3        | DNI                                   | X   | 3        | DNI                                   | X   |
| 4        | DNI                                   | X   | 4        | DNI                                   | X   |
| 5        | DNI                                   | X   | 5        | DNI                                   | X   |

| Specimen | <u>Flame Spread Fill</u><br>(seconds) | Without Nap<br>(Plain Surface)<br><b>FACE</b> | Specimen | <u>Flame Spread Fill</u><br>(seconds) | Without Nap<br>(Plain Surface)<br><b>BACK</b> |
|----------|---------------------------------------|---|----------|---------------------------------------|---|
| 1        | DNI                                   | X   | 1        | DNI                                   | X   |
| 2        | DNI                                   | X   | 2        | DNI                                   | X   |
| 3        | DNI                                   | X   | 3        | DNI                                   | X   |
| 4        | DNI                                   | X   | 4        | DNI                                   | X   |
| 5        | DNI                                   | X   | 5        | DNI                                   | X   |

- **DNI - Did not ignite when exposed to test ignition source**
- **IBE - Ignited but extinguished before burning through stop cord.**
- **SF - Surface flash only; stop cord not burned & no burning/charring/fusing of the base fabric.**
- **TSF - Timed surface flash; stop cord burned, but no burning/charring/fusing of the base fabric.**


**Requirements: With nap** - Minimum flame spread of any individual specimens shall be less than 7 seconds.

**Requirements: Without nap** - Minimum flame spread of any individual specimens shall be less than 3.5 seconds.

**Conclusion:** The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Lab Manager: Sallie Cotey

  
 Lab Technician: Jennifer Friend