



96-D Allen Boulevard  
 Farmingdale, New York 11735-5626 USA  
 Tel. +1 (631) 293-8944 Fax +1 (631) 293-8944  
 e-mail: info@govmark.com

Received: 04/06/2007	Completed: 04/10/2007	Letter: X	rb	P.O.#: 62363	Test Report #:	2-67158-0-
Client's Identification	TRIBUTE 5071					
Tested For: Judy M. Cockrell, Lab Mgr.				Key Test: NFPA 260 Cover Fabric (BLDG)		85
				Tel:	Ext:	
				Fax:		

Category: NFPA 260 Fabric      Specifier: Bldg. Codes      PC: 4H      /jd

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture; Cover Fabric Test

RESULTS:

Specimen #	TEST		RETEST (If Required)	
	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)
1	No	20		
2	No	20		
3	No	20		

ABBREVIATION WHICH MAY BE USED:

SE: Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.

REMARKS: None.

CLASSIFICATION SYSTEM:

Class I - For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)

Class II - For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

Class I rating;     Class II rating



The  
Organization, Inc.

96-D Allen Boulevard  
Farmingdale, New York 11735-5626 USA  
Tel. +1 (631) 293-8944 Fax +1 (631) 293-895  
e-mail: info@govmark.com

Received: 04/06/2007	Completed: 04/10/2007	Letter: X	rb	P.O.#: 62365	Test Report #:	2-67158-0-
Client's Identification	TRIBUTE 5071					
Tested For: Judy M. Cockrill, Lab Mgr.				Key Test: NFPA 260 Cover Fabric (BLDG)		85
				Tel:	Ext:	
				Fax:		

CODE INFORMATION: In accordance with --

- (1) The 2006 Edition of the NFPA Life Safety Code 101, paragraph 10.3.2.1(1); and
- (2) The 2006 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1 and 805.3.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

- Detention or correctional occupancy
- Health care occupancy
- Residential board & care occupancy

In certain situations an exception is made if the rooms or areas are sprinklered.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 260.

-----  
AUTHORIZED SIGNATURE  
THE GOVMARK ORGANIZATION, INC. /jd