



CAL117, Section E, Part I - Upholstery Fabrics

Laboratory Testing:

Applied Textiles
555 76th Street
Grand Rapids, MI 49509
(616) 559-6123
(616) 559-6119 fax

Company Submitting Test:

Pollack & Associates
150 Varick Street
New York, NY 10013

Product Identification: **6005 Bark Silk**

Date Samples Received: 02-10-99

Test Report #: 41274

	Flame Spread Warp (seconds)	With Nap	Without Nap
Specimen			
1	NS		X
2	NS		X
3	NS		X
4	NS		X
5	NS		X

	Flame Spread Fill (seconds)	With Nap	Without Nap
Specimen			
1	NS		X
2	NS		X
3	NS		X
4	NS		X
5	NS		X

* NS - No flame spread

Requirements: With nap - Minimum flame spread of any individual specimens shall be less than 7 seconds.


Requirements: Without nap - Minimum flame spread of any individual specimens shall be less than 3.5 seconds.

Conclusion: The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Testing Completed: 02-10-99

Test Supervisor: Sallie Cotey


Lab Technician, Sue Axel