

CERTIFICATE OF TESTING

For The Account Of:

Pollack

150 Varick Street

New York, NY 10013-1218 Contact: Larry Hoysic

DATE: July 27, 2005

CERTIFICATE (ORDER) NO.: 13623

CLIENT'S IDENTIFICATION:

Starbeam 6032

CAL117, Section E, Part I - Upholstery Fabrics (CS 191-53) Plain Surface

Specimen	Flame Spread Warp (seconds)	Without Nap (Plain Surface) FACE	Specimen	Flame Spread Warp (seconds)	Without Nap (Plain Surface) BACK
1	DNI	X	1	DNI	X
2	DNI	X	2	DNI	X
3	DNI	X	3	DNI	X
4	DNI	X	4	DNI	X
5	DNI	X	5	DNI	X

Specimen	Flame Spread Fill (seconds)	Without Nap (Plain Surface) FACE	Specimen	Flame Spread Fill (seconds)	Without Nap (Plain Surface) BACK
1	DNI	X	1	DNI	X
2	DNI	X	2	DNI	X
3	DNI	X	3	DNI	X
4	DNI	X	4	DNI	X
5	DNI	X	5	DNI	X

- DNI Did not ignite when exposed to test ignition source
- IBE Ignited but extinguished before burning through stop cord.
- SF Surface flash only; stop cord not burned & no burning/charring/fusing of the base fabric.
- TSF Timed surface flash; stop cord burned, but no burning/charring/fusing of the base fabric.

Requirements: With nap - Minimum flame spread of any individual specimens shall be less than 7 seconds.

Requirements: Without nap - Minimum flame spread of any individual specimens shall be less than 3.5 seconds.

Conclusion: The above results indicate **COMPLIANCE** with the stated requirements.

I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Technical Bulletin 117, Section E, Part I Upholstered Fabrics dated January 1980.

Lab Manager: Sallie Cotey

Jab Technician: Jennifer Friend

F-310-A